



Tactical Starlink Sentry

Ideally suited for rapid communications restoration at operations centers, substations, and remote areas



Applications

- Secure backhaul for mission-critical communications
- Support field operations and incident command posts
- Broadband service for exercises and special events
- Land Mobile Radio (LMR) gateway

Sentry at a Glance

01 Deploy

Mobile deployable communications solution that is cost-effective, easy to transport, and requires no training to setup.

02 Connect

Whether you're supporting emergency communications or hosting a special event, establish secure high-speed connectivity anywhere in minutes.

03 Restore

When infrastructure is depleted, restore mission-critical communications circuits in all weather conditions.



(240) 249-2084



info@onecogito.com



44070 Airport View Drive
Hollywood, MD 20636

Visit Us:

cogitoinnovations.com

GENERAL SPECIFICATIONS
Dimensions: 27.75"L x 26.25"W x 12.15"H
Weight (CT-110): 52.8 lb
IP67 Physical Ports: Ethernet Power
Maximum Power: 170W (120W Typical)
Operating Temperature: -20 °C to +50 °C
Ingress Protection: IP65 (Lid Off) IP67 (Lid On)

SYSTEM CONFIGURATION											
CTABC-X (Example: CT-100-A)											
A. POWER	1: 100-240VAC 2: 12VDC 3: 24VDC 4: 48VDC										
B. NETWORK	0: WIRED ETHERNET (ALL MODELS) 1: WI-FI 2: WI-FI W/ SD-WAN										
C. BACKUP POWER	0: NONE 1: INTEGRATED BATTERY CHARGER (REQUIRES EXTERNAL BATTERY PACK - SOLD SEPARATELY)										
X. COLOR	<table border="0"> <tr> <td>A: BLACK</td> <td>F: ORANGE</td> </tr> <tr> <td>B: OLIVE DRAB</td> <td>G: RED</td> </tr> <tr> <td>C: TAN</td> <td>H: DK BLUE</td> </tr> <tr> <td>D: DK YELLOW</td> <td>J: LT BLUE</td> </tr> <tr> <td>E: LT YELLOW</td> <td>K: WHITE</td> </tr> </table>	A: BLACK	F: ORANGE	B: OLIVE DRAB	G: RED	C: TAN	H: DK BLUE	D: DK YELLOW	J: LT BLUE	E: LT YELLOW	K: WHITE
A: BLACK	F: ORANGE										
B: OLIVE DRAB	G: RED										
C: TAN	H: DK BLUE										
D: DK YELLOW	J: LT BLUE										
E: LT YELLOW	K: WHITE										

